

Aquanir ADVANCE

English translation of manufacturer TDS | Original revision: 06/2025

PRODUCT DESCRIPTION

Water-based acrylic wall paint developed with USP technology for a smooth, uniform wall appearance. Intended for interior and exterior walls. Provides especially high coverage, excellent hiding and very high washability. Cleans easily without damaging the paint texture. Compared with standard paint, it is stated to be twice as resistant to heavy scrubbing, UV radiation and abrasion. Easy and user-friendly to apply, durable and shade-retentive. Aquanir ADVANCE carries Israeli Standard 1945 and a Green Label.

USES

For interior and exterior walls including plaster, concrete, cement boards, gypsum-board walls and similar substrates, after suitable surface preparation.

SURFACE PREPARATION

Clean the surface thoroughly from old, loose or peeling paint, dust, lime, oils and other contaminants. Ensure remaining existing paint is firmly bonded. Existing interior walls: repair defects with Nirlat Rockbond / Gold Bond / Proximo+ and, after full drying, apply Aqua Primer. Existing exterior walls: repair defects with Nirlat Altek Exterior; after full drying apply Primer X2. New walls with white plaster: apply Aqua Primer for interior walls or Primer X2 for exterior walls.

DRYING

Touch dry: approx. 1 hour. Between coats: approx. 2 hours. Final drying / ready for further work: 24 hours. Values stated for 25°C and approximately 80% relative humidity.

APPLICATION INSTRUCTIONS

The product is supplied in two finish levels: matte and silk. For the silk finish, application over a well-smoothed substrate is recommended for the best appearance. Stir well before use and apply two coats by roller, brush or airless spray. Wait about 2 hours between coats under normal weather conditions.

DILUTION

Dilute with water up to 20% as required and according to the coat.

TECHNICAL DATA

Technical item	Value
Color	All shades in the Nirlat color fan
Finish	Decorative / premium appearance; available in matte and silk
Shelf life / storage	24 months in a closed pail, in a cool, shaded and dry place
Cleaning	Tools and hands: water and soap
Package sizes	5 L, 15 L
Maximum coverage	Approx. 150 m ² per package in one coat (as stated in the source TDS)

LIMITATIONS / SAFETY

Do not apply below 7°C, or when rain and/or a sandstorm is expected within 72 hours.

Before use, verify proper surface preparation and product suitability for the intended application. The user must determine suitability for their needs. Nirlat reserves the right to update technical data. Do not mix or tint with materials not recommended by Nirlat. For warnings and safety instructions, consult the product label and SDS.

TRANSLATION NOTICE

This document is an English translation prepared for Colorstorm from Nirlat's Hebrew manufacturer TDS. It is provided for reference and does not replace the manufacturer's original Hebrew document, product label, SDS, or project-specific technical advice.

Original manufacturer source: <https://nirlat.com/wp-content/uploads/2021/01/רצום-ADVANCE-.pdf>