

Aquanir EXTRA

English translation of manufacturer TDS | Original revision: 07/2023

PRODUCT DESCRIPTION

Water-based acrylic paint with a matte finish, developed with USP technology to provide a smooth and uniform wall appearance. Intended for interior and exterior walls. Provides particularly high coverage and excellent hiding, is washable and easy to clean without damaging the paint texture, is easy and user-friendly to apply, durable, and retains its shade over time. Aquanir EXTRA carries Israeli Standard 1945 and a Green Label.

USES

For interior and exterior walls including plaster, concrete, cement boards, gypsum-board walls and similar substrates, after suitable surface preparation.

SURFACE PREPARATION

Clean the surface thoroughly from foreign matter such as old, loose or peeling paint, dust, lime and oils. Make sure any existing paint remaining on the wall is firmly bonded. Existing interior walls: repair defects with Nirlat Rockbond / Gold Bond / Proximo+ as applicable; after full drying apply Aqua Primer. Existing exterior walls: repair defects with Nirlat Altek Exterior; after full drying apply Primer X2. New walls with white plaster: first apply Aqua Primer for interior walls or Primer X2 for exterior walls.

DRYING

Touch dry: approx. 1 hour. Between coats: approx. 2 hours. Final drying: 24 hours. Values stated for 25°C and approximately 80% relative humidity.

APPLICATION INSTRUCTIONS

Stir well before use. Apply two coats by roller, brush or airless spray. Wait approximately 2 hours between coats under normal weather conditions.

DILUTION

Dilute with water up to 30%, according to substrate and coat.

TECHNICAL DATA

Technical item	Value
Color	All shades in the Nirlat color fan
Finish	Matte
Shelf life / storage	24 months in a closed pail, in a cool, shaded and dry place
Cleaning	Tools and hands: water and soap
Package sizes	1, 5, 10, 15, 18 L
Maximum coverage	Approx. 13 m ² /L in two coats

LIMITATIONS / SAFETY

Do not apply when the temperature is below 7°C. For exterior use, do not apply when rain and/or a sandstorm is expected within 72 hours.

Before use, verify proper surface preparation and product suitability for the intended application. The user must determine suitability for their needs. Nirlat reserves the right to update technical data. Do not mix or tint with materials not recommended by Nirlat. For warnings and safety instructions, consult the product label and SDS.

TRANSLATION NOTICE

This document is an English translation prepared for Colorstorm from Nirlat's Hebrew manufacturer TDS. It is provided for reference and does not replace the manufacturer's original Hebrew document, product label, SDS, or project-specific technical advice.

Original manufacturer source: https://nirlat.com/wp-content/uploads/2021/01/רינווקא-רצומ-ףד/EXTRA_-004.pdf