


DECOPRIMER

Decorative Paint Primer

DECOPRIMER is a textured primer used on interior and exterior surfaces to enhance the adhesion of decorative products to the substrate.



Provides a textured surface that increases mechanical adhesion.

Adheres strongly to the surface, preparing the base for the application of decorative materials.

Has high coverage.

It is water-based, friendly to human health and the environment.



CONTENT: Acrylic-based - water-based



PACKAGING: 1 L ; 2,5 L ; 15 L



THINNING: With 25-30% clean water



DRYING TIME: Drying Time Touch dry (at 23°C): 2-3 hours
*drying time may be longer at higher relative humidity and lower temperature.



PRIMER: -



Fully Dry: 24 hours



APPLICATION TOOL: Roller



COLORING: -



NUMBER of COATS: 1



STORAGE and SHELF LIFE:
Can be stored for 2 years between +5°C and +35°C, in its unopened packaging, in a cool and dry place protected from direct sunlight.



VOC:
Limit value EU (Directive 2004/42/EC)
Category A/G: Primers (water-based): 30 g/l (2010)
DECOPRIMER: contains a maximum of 28.3 g/l VOC.

CONSUMPTION - Single Coat : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.



1 L covers 10.5-15 m²,
1 kg covers 6.5-10 m².

Paint consumption per 1 m² surface: 65-100 ml or 100-150 g.

APPLICATION AREA

It is used as a primer for acrylic-based paint and coating materials applied on mineral surfaces such as concrete, aerated concrete, pressed brick, or fine plaster, both on interior and exterior walls.

SURFACE PREPARATION

All dirt, oil, flaking paint, and dust should be removed from the surfaces before application. Surface imperfections should be repaired using San Deco Acrylic Putty Fine for interiors and San Deco Acrylic Putty Coarse for exteriors.

SURFACE CONDITIONS

During application and until the products are completely dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

During application, ambient humidity should be below 75%.

The surface moisture content should be below 10%.

APPLICATION

Decoprimer should be diluted with 25-30% clean water by volume and mixed homogeneously before application.

The product should be applied to the surface in a single coat using a roller.

HAZARD & PRECAUTIONARY STATEMENTS AND DESCRIPTIONS

H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment (see label).

P272: Contaminated work clothing should not be allowed out of the workplace.



Complies with TS 13744.

This technical data sheet is prepared based on laboratory data under normal conditions; for any details not sufficiently covered above, please consult technical personnel. Otherwise, the manufacturer cannot be held responsible for errors arising from insufficient information. Our company reserves the right to change this information. If necessary, detailed information regarding the health, safety, and transportation risks and precautions of the products can be found in the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds conformity certificates for ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.