

DECOSATIN

Silicone-Added Water-Based Semi-Matt Interior Wall Paint

DECOSATIN is a silicone-added, semi-matt decorative interior wall paint developed for indoor use.



Thanks to its cleanable feature, it can be easily cleaned and does not retain stains.

It has high coverage.

It is water-based, environmentally and human health friendly.

 CONTENT: Acrylic-based – water-based – silicone added	 PACKAGING: 2,5 L ; 7,5 L ; 13,5 L ; 15 L
 THINNING: Dilute with a maximum of 5-10% clean water	 DRYING TIME: Drying Time Touch dry (at 23 °C): 5-6 hours <i>*drying time may be longer at higher relative humidity and lower temperature.</i>
 PRIMER: San Deco Uniprimer	 Fully Dry: 24 hours
 APPLICATION TOOL: Roller, brush, spray	 COLORING: Vision, Liberte Art, RAL, NCS
 NUMBER of COATS: 2	 VOC: EU Limit Value (Directive 2004/42/EC) Category A/A: Interior matt walls and ceilings (water-based): 30 g/l (2010) BAHARIA: maximum content 26.8 g/l VOC
 STORAGE and SHELF LIFE: Can be stored unopened in a cool, dry place, protected from direct sunlight, between +5 °C and +35 °C for 2 years.	

CONSUMPTION - Single Coat : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.



1 L covers 11-16 m²,
1 kg covers 7.5-11 m².

Paint consumption per m²: 65-95 ml and 90-135 g.

APPLICATION AREA

It is applied on interior walls to properly prepared mineral surfaces such as black plaster, concrete, cement board, gypsum panel, and previously painted surfaces together with a suitable primer.

SURFACE PREPARATION

After cleaning all kinds of dirt, grease, blistered paints, and dust from the surfaces to be applied, surface defects should be repaired with San Deco Acrylic Fine Putty, followed by priming with San Deco Uniprimer.

It is recommended to use a primer in the same color as the chosen facade color.

SURFACE CONDITIONS

During application and until the products are completely dry, the ambient and surface temperature should be maintained between a minimum of +5°C and a maximum of +35°C.

During application, the ambient humidity should be kept below 75%.

The moisture content of the surface to be applied should be below 10%.

APPLICATION

Before application, Decosatin should be diluted with a maximum of 5-10% clean water by volume and mixed homogeneously.

The product is applied to the surface in two coats using a roller, brush, or spray method. At least 5 hours should be waited between coats.

If more than one batch number is used in the same project, it is recommended to mix the batches evenly before application application to prevent batch-based differences.

HAZARD & PRECAUTIONARY STATEMENTS AND EXPLANATIONS

H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment is required (see label).
P272: Contaminated clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).



Complies with TS 5808/2012.



Complies with G notification.

Since this technical data sheet is prepared based on laboratory data under normal conditions, please consult technical personnel for details not sufficiently covered above. Otherwise, the manufacturer shall not be held responsible for errors resulting from insufficient information. Our company reserves the right to change this information. When necessary, detailed information on the health, safety, and transportation risks and precautions of the products can be found in the Material Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds compliance certificates for ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.